

AMENDMENTS TO THE CLAIMS

1. (Currently amended) A device for absorbing or dispensing a liquid, said device comprising a liquid reservoir and an activatable porous membrane, said membrane being impermeable to gas and liquid, and, upon activation, thereafter allowing liquid to pass therethrough, the reservoir comprising an inlet, wherein the reservoir is at least partly occupied by a porous bulk material, the membrane being hermetically sealed to or around the reservoir so that liquid passing through the inlet must pass across the membrane, said membrane being coated with a soluble layer, said soluble layer being dissolved upon contact with liquid.
2. (Original) A device according to claim 1 wherein the membrane has an average pore size which is greater than 10 micrometers.
3. (Original) A device according to either claim 1 or 2 wherein the membrane has a pore size distribution is such that 95% of the pores have a size of no more than 100 micrometers.
4. (Original) A device according to any of claims 1 to 3 comprising an inner porous bulk material within an outer membrane, the membrane being hermetically sealed by means of a membrane to membrane seal.
5. (Original) A device according to claim 1 wherein the bulk material is replaced by a void space, characterised in that the porous membrane has an average pore size of from 10 to 100 micrometers.
6. (Original) A device according to claim 5 wherein the liquid reservoir is defined by a wall region, and wherein the volume of the liquid reservoir is variable.
7. (Original) A device according to claim 6 wherein the volume of the liquid reservoir is varied by flexibly deforming the wall region.
8. (Original) A device according to claim 7 wherein the volume of the liquid reservoir is varied by the action of a piston.
9. (Original) A device according to any of the previous claims wherein the membrane has a bubble point pressure of at least 1 kPa when measured at ambient temperature and pressure using 0.03% solution of Triton X-100 in distilled water as the standard test liquid.

10. (Original) A device according to claim 9 wherein the membrane has a bubble point pressure of from 8 kPa to 50 kPa.
11. (Original) A device according to any of the previous claims wherein the membrane is a woven mesh or apertured film.
12. (Previously added) A device according to claim 1 wherein said membrane is permanently activated upon contact with liquid.
13. (Canceled)
14. (Previously added) A device according to claim 12 wherein said membrane is impermeable to gas both before and after activation.
15. (Previously added) A device according to claim 12 wherein said membrane is permeable to both gas and liquid after activation.
16. (Previously added) A device for containing or dispensing a gas, said device comprising a gas reservoir having an inlet therethrough, and an activatable porous membrane, said membrane spanning said inlet so that gas passing through said inlet passes through said membrane, said membrane being impermeable to gas and liquid, and, upon activation, thereafter allowing gas to pass therethrough, said membrane being coated with a soluble layer, said soluble layer being dissolved upon contact with liquid.
17. (Currently amended) A device according to claim 16 wherein said membrane is permanently activated ~~upon contact with gas.~~
18. (Canceled)
19. (Currently amended) A device according to claim ~~18~~17 wherein said soluble layer comprises polyvinyl alcohol.
20. (Canceled)